



Client:

Morrison Telecom Services

Project:

Dotcliffe Road,
Barnoldswick
BB18 6TJ

Title:

Road Closure

DESIGN INPUTS

(FOR REFERENCE RELATE TO CONTROL DOCUMENT: F-012-DesignRefs iss 1)

D1

☐

D2

☐

D3

☐

D4

☐

D5

☐

D10

☐

D10 - OTHER? PLEASE STATE:

Key:

Traffic sign

Traffic cone/cylinder

Traffic signals to Diagram 3000.1

Pedestrian barrier

Stop/Go board (P7023/P7024)

Work Area

Area of road closed

Diversion Route

Temporary vehicle restraint barrier

This Drawing is the property of
Dutton Traffic Management Services.

It MUST NOT be copied in part or sent to
a third party without written permission.

DETAIL B

(B)

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
2) 45° tapers have 1.5m spacing, no relaxations.
3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C1

(C1)

Single/Dual carriageway 40mph or less - 450mm traffic cones.
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Drawn:

Checked:

Liam Steen

Gary Mainwaring

26/11/2022

Rev:

DTMS-LS259

Original drawing size A3 - NTS